

REBAR RADIUS / RING FORMING MACHINE



REBAR ARC-RADIUS FORMING MACHINE IS PERFECT WHEN REBARS ARE TO BE FORMED IN LARGE ARC-RADIUS OR RINGS. THE PLC HELPS SET THE MACHINE TO FORM THE DESIRED PROFILE. AND IT WILL THEN STORE THE PROGRAMS FOR FUTURE USE. A ROBUST ELECTRO-HYDRAULIC DRIVE POWERS THE MACHINE WHICH ENSURES EXCELLENT PRODUCTIVITY, LIFECYCLE AND VERY LOW MAINTENANCE.

SPECIFICATIONS AND FEATURES

MODEL	MAX BAR SIZE (GRADE 500)	FORMING SPEED M/MIN	POWER Kw (HP)	MACHINE SIZE (LXBxHT) MM	MACHINE WEIGHT KGS
RA-B20	METRIC-20	8 – 18	2.3 (3)	800x600x1100	350
RA-B32	METRIC-32	8 – 18	7.8 (10)	1100x900x1200	800

THE MACHINE CAPACITY IS EVALUATED BY THE MINIMUM DIAMETER RING IT CAN FORM OF A PARTICULAR BAR SIZE:
BAR SIZE X MINIMUM RING DIAMETER : RA-B20: 20X900 / 16X600 RA-B32: 32X2000

- ✓ VARIABLE OPERATING SPEED 8-18 METERS PER MIN
- ✓ MULTIPLE BAR FORMING CAPABLE DEPENDENT ON BAR SIZE AND MACHINE GEOMETRY
- ✓ PLC CONTROLS OPTIONAL : PLC MAKES THE MACHINE MORE USER FRIENDLY
- ✓ COVERS AND SAFETY SYSTEMS ENSURES SAFE WORKING CONDITIONS

WATCH VIDEO : [HTTPS://YOUTU.BE/BLQDKMRNS0A](https://youtu.be/BLQDKMRNS0A)

MACHINE IS AVAILABLE WITH / WITHOUT PLC CONTROLS

SPECIFICATIONS SUBJECT TO CHANGE



**CONSOLIDATED
MACHINES**

HYDRAULICS • HYDRO-PNEUMATICS
CONSTRUCTION EQUIPMENT

H-137 Ansa Industrial Estate, Sakivihar Road. Mumbai 400 072 India. Tel: +91-22-2847 0036 / 2851 8625
Mob : +91 98200 77035 / 98200 79035 / 92465 68775

consolidatedmachines@gmail.com <http://www.consolidatedmachines.net> <http://www.rebarindia.com>